



AirTrack

DP-1 – DESKTOP THERMAL TRANSFER BAR CODE PRINTER

THE PERFECT COMBINATION OF PERFORMANCE AND VALUE



KEY FEATURES

- Perfect size – space saving design
- USB 2.0, serial, parallel and Ethernet interfaces are standard
- High quality double-walled clamshell design
- Fast 200 MHz Processor
- Standard memory of 4 MB Flash, 8 MB SDRAM
- SD card reader for memory expansion up to 4 GB
- Easy ribbon loading & media loading
- Powerful AirTrack firmware includes popular Zebra™ languages, file manager, BASIC programming, stand-alone programming
- 2-year limited warranty

APPLICATIONS

- Point-Of-Sale
- Product Marking
- Receipt / Coupon Printing
- Compliance Labeling
- Asset Tracking
- Document Management
- Shipping / Receiving
- Inventory Control
- Specimen Labeling
- Patient Tracking

DP-1 - DESKTOP THERMAL TRANSFER BAR CODE PRINTER

PRINTER MODEL	DP-1
Resolution	8 dots/mm (203 DPI)
Printing method	Thermal Transfer & Direct Thermal
Max. print speed	102 mm (4")/second
Max. print width	108 mm (4.25")
Max. print length	2,286 mm (90")
Enclosure	Double-walled plastic
Physical dimension	202mm (W) x 173 mm (H) x 258 mm (D) 7.95" (W) x 6.81" (H) x 10.16" (D)
Weight	2.3 kg (5.07 lbs)
Label roll capacity	127 mm (5") OD
Ribbon	110 m long, max. OD 40 mm, 0.5" core (ink coated outside)
Ribbon width	40 mm ~ 110 mm (1.57" ~ 4.33")
Processor	32-bit RISC CPU
Memory	4 MB Flash memory 8 MB SDRAM SD Flash memory card reader for Flash memory expansion, up to 4 GB
Interface	USB 2.0 RS-232 Centronics Internal Ethernet, 10/100 Mbps Bluetooth (user option)
Power	External universal switching power supply Input: AC 100-240V, 2.5A, 50-60 Hz Output: DC 24V, 2.5A, 60W
Operation switch, button LED	1 power switch, 1 feed button & 1 LED (3 colors: green, amber & red)
Sensors	Gap transmissive sensor Black mark reflective sensor (position adjustable) Head open sensor Ribbon end sensor
Internal fonts	8 alpha-numeric bitmap fonts Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
Bar code	1D bar code: Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, GS1 DataBar, Logmars, Code 11 2D bar code: PDF-417, Maxicode, DataMatrix, QR code, Aztech
Font and barcode rotation	0, 90, 180, 270 degree
Printer language	AirTrack Firmware™ (Compatible to EPL, ZPL, ZPL II)
Media type	Continuous, die-cut, tag & fan-fold (outside wound)
Media width	20 ~ 112 mm (0.79" ~ 4.4")
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)
Media core diameter	25.4 ~ 38.1mm (1" ~ 1.5")
Label length	10 ~ 2,286 mm (0.39" ~ 90")
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Safety regulation	FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TÜV/Safety, CCC
Environmental concern	Comply with RoHS, WEEE
Accessories	Windows labeling software CD disk Quick start guide External universal switching power supply USB cable Power cord
Limited warranty	Printer: 2 years Print head: 25 km (1 million inches) or 12 months which comes first Platen: 50 km (2 million inches) or 12 months which comes first
Factory options	N/A
Dealer options	Guillotine cutter (full cut or partial cut)
User options	Peel-off module External media hanger with 3" OD label spindle Bluetooth module (serial interface)



 AirTrack

Phone: +1 855-235-1718